

METHOD AND APPARATUS FOR SUPPORTING SOFTWARE

FIELD OF THE INVENTION

The present invention relates to software support systems. More particularly, embodiments of the present invention relate to methods, apparatus, and computer program code for automatically supporting and correcting software.

BACKGROUND OF THE INVENTION

Despite continued and valiant efforts by software manufacturers, software users commonly encounter software errors. Errors can arise from a number of different conditions including, for example, incompatibilities between different software applications, user errors, memory errors, and the like. Often, software manufacturers produce patches or fixes to software upon learning of the error. However, it is quite difficult to disseminate these patches or fixes to thousands or even millions of geographically diverse users after they have already commenced use of the software. Typically, software manufacturers attempt to notify users of the need to upgrade or receive a patch by publicizing new releases or service packs, which interested users can download and install by, for example, visiting the manufacturer's Website. Some manufacturers, such as manufacturers of computer security software which are frequently updated to include protections against new computer viruses, install timers in the software to notify users when it is time for them to update the software. The update occurs when the user contacts a Website of the manufacturer to initiate an update.

Many users, however, do not become aware of the need for a patch until after they have experienced difficulty in operating the software. Other users never become aware of the need to update their software and simply live with defective code. It can be frustrating and inefficient for these users to

encounter errors and other difficulties when operating software, particularly where a patch or fix is available. It would be desirable to provide a system and method which allows automatic correction and support of software where the user is not required to take actions to contact a manufacturer for an update or
5 patch.

Other types of errors can occur while users operate software. For example, due to the complexity of many software packages, users may not know how to properly or most efficiently use the software. It would be
10 desirable to provide a system and method which monitors for user inefficiencies or operational errors and which automatically provides assistance to those users.

15 SUMMARY OF THE INVENTION

Embodiments of the present invention provide a system, method, apparatus, and computer program code for supporting software. In one embodiment, a method of supporting a software program includes receiving
20 error data identifying an error in software on a user device. A patch for the error is identified and forwarded to the user device to update the software program.

According to one embodiment, the patch is identified and provided from
25 a central service. In other embodiments, the patch is identified and provided from a software provider. In yet another embodiment, the patch is identified and provided locally from a data storage device of the user device.

According to one embodiment, the user device is monitored for errors
30 before the error is identified. A variety of different errors may be monitored for, identified, and corrected using embodiments of the invention. For

example, the error may be a user error, including a user failure to correctly or efficiently use software. The error may be a media error (e.g., a defect in a CDROM drive or other media), an application program error, or other defect.

- 5 In one embodiment, information identifying the error and information identifying a condition under which the error occurred are used to identify and provide a patch.

- 10 According to one embodiment, a patch is forwarded to the user device along with supporting information such as, for example, installation instructions, use instructions, helpful tips, or advertisements.

- 15 According to one embodiment, the patch is provided from a service provider which has access to a wide variety of patches for a number of different application programs. In one embodiment, the service provider receives payment for patches provided, e.g., from the user or from the software manufacturer.

- 20 With these and other advantages and features of the invention that will become hereinafter apparent, the nature of the invention may be more clearly understood by reference to the following detailed description of the invention, the appended claims and to the several drawings attached herein.

BRIEF DESCRIPTION OF THE DRAWINGS

- 25 FIG. 1 is a block diagram of a system consistent with the present invention;

- 30 FIG. 2 is a block diagram of one embodiment of the user device depicted in FIG. 1;

Ans A1

~~FIG. 3 is a block diagram of one embodiment of the controller depicted in FIG. 1;~~ *A1*

Ans A2

~~FIG. 4 is a tabular representation of a portion of a patch database according to an embodiment of the present invention;~~ *A2*

Ans A3

~~FIG. 5 is a tabular representation of a portion of an instruction database according to an embodiment of the present invention;~~ *A3*

Ans A4

~~FIG. 6 is a block diagram of one embodiment of the vendor device depicted in FIG. 1; and~~ *A4*

FIG. 7 is a flow diagram illustrating an exemplary process for supporting software according to an embodiment of the present invention.

DETAILED DESCRIPTION

Applicants have recognized that there is a need for a system, method, apparatus, and computer program code for supporting software systems which overcomes drawbacks of existing systems

For clarity and consistency, a number of terms are used herein. As used herein, the term "error" refers to any condition indicating a failed action of a software program including, for example: general protection faults; failed requests; hard or soft errors, and the like. Further, as used herein, the term "error" also includes user errors including user inefficiencies in operating software and/or user input errors. "Error" also refers to errors in data such as those produced by a scratch on media such as a CDROM, digital video disk (DVD), or, more generally, those present in a corrupted data file.

As used herein, the term "patch" is used to refer to code used to update, fix, or otherwise modify a software program and includes general-purpose fixes that replace or alter portions of a program. "Patch", as used herein, also refers to code, instructions, or other information provided to a user of a user device to facilitate correction of a user error. Further, "patch" may also include data or other information used to correct a media error such as a defect on a CDROM.

Prior to a detailed description of systems, devices, and processes of the invention, an illustrative example will now be presented to facilitate understanding of embodiments of the present invention. In one embodiment, features of the present invention may be used to monitor for, detect, and correct errors in application software programs such as a word processing program operated by a user at a user device such as a home or office personal computer (PC). Embodiments of the present invention monitor operation of the PC and the word processing program to detect errors (including hard or soft application errors or user errors in operation of the program). Once an error is detected, the error is identified, and corrective action is identified. Identification of the error and the corrective action may be performed by a central service bureau (operating a controller described below), by the PC, by the software vendor, or by a combination of the entities. If a fix (such as a "patch") is available, the fix is forwarded to the user device and installed. In some embodiments, the user or the software vendor may pay for the service (e.g., by paying a fee for each fix or a flat rate for the service).

Other types of errors may also be monitored, detected, and corrected. For example, a user operating a spreadsheet program on a PC may be inefficiently using the program when he attempts to sum a large column of numbers by individually adding each number in the column. Embodiments of the invention may be configured to monitor for such an inefficiency, and

propose a fix for the inefficiency. Again, the fix may be identified and retrieved from the user's PC, from a central service bureau, from the software vendor or from a combination of the three entities. The fix may simply be instructions to the user on how to more efficiently perform the action.

5

These and other features will be discussed in further detail below, by first describing the system, individual devices, exemplary databases and processes according to embodiments of the invention.

10

System

Referring first to FIG. 1, a block diagram depicting a system 100 for supporting software is shown. System 100, as depicted, includes a number of user devices 200 and a number of vendor devices 300 in communication with a controller 400. In some embodiments, one or more vendor devices 300 may communicate directly with one or more user devices 200.

In one embodiment, user devices 200 are personal computers or other computing devices operating one or more software programs such as any commercially available application program (e.g., a word processing program, a spreadsheet program, a graphics program, etc.). In operation, a user of user device 200 may experience one or more errors which disrupt his or her use of the software. According to embodiments of the present invention, these errors are detected and information about the error is forwarded to, e.g., controller 400 which uses the information to identify a patch for the error. The patch is transmitted to user device 200 to enable the user to continue to operate user device 200 with a minimal amount of disruption. In one embodiment, controller 400 is a Web-server operated by a service provider and storing and maintaining a number of different patches for one or more software manufacturers. In one embodiment, controller 400 receives patches

06765572 021601

from software vendors operating vendor devices 300. In some embodiments, vendor devices 300 may provide patches directly to user devices 200.

As used herein, devices (such as user devices 200, vendor devices
5 300 and controller 400) may communicate, for example, via a communication network, such as a Local Area Network (LAN), a Metropolitan Area Network (MAN), a Wide Area Network (WAN), a proprietary network, a Public Switched Telephone Network (PSTN), a Wireless Application Protocol (WAP) network, a wireless network, a cable television network, or an Internet Protocol (IP)
10 network such as the Internet, an intranet or an extranet. Moreover, as used herein, communications include those enabled by wired or wireless technology.

In one embodiment of the present invention, user devices 200 and
15 vendor devices 300 communicate with a remote, Web-based controller 400 (e.g., a server) via the Internet. Although some embodiments of the present invention are described with respect to information exchanged using a Web site, according to other embodiments information can instead be exchanged, for example, via: a direct wired or wireless telephone connection, electronic
20 mail, a WEBTV® interface, a cable network interface, and/or a wireless communication system.

Note that although a single controller 400 is shown in FIG.1, any number of controllers 400 may be included in system 100. Similarly, any
25 number of the other devices described herein may be included in system 100 according to embodiments of the present invention. Note that the devices shown in FIG. 1 need not be in constant communication. For example, user device 200 may only communicate with controller 400 via the Internet when appropriate (e.g., when, as described further below, an error occurs in
30 software run on user device 200). Embodiments of each of the devices,

including user device 200, vendor device 300 and controller 400 will now be described.

5 Devices

1. User Device

FIG. 2 illustrates an embodiment of user device 200. In one
10 embodiment, user device 200 is a personal computer (PC) operating one or
more software programs which are maintained, supported or corrected using
embodiments of the present invention. User device 200 may be any device
capable of performing the various functions described herein. User device
200 may be, for example: a Personal Computer (PC), a portable computing
15 device such as a Personal Digital Assistant (PDA), a wired or wireless
telephone, a one-way or two-way pager, an interactive television device, a
gaming terminal (e.g., a SONY PLAY STATION® video game terminal), or
any other appropriate computing, storage and/or communication device.

20 User device 200 comprises a processor 210, such as one or more
Intel® Pentium® processors. Processor 210 is coupled to a communication
port 220 through which processor 210 communicates with other devices, such
as, for example, one or more controllers 300. Processor 210, via
communication port 220, may also communicate with one or more remote
25 vendor devices 300. Communication port 220 may include hardware and
software facilitating communication with other devices using wired or wireless
techniques, or a combination of different techniques. For example,
communication port 220 may be one or more of: a network adapter, a modem,
a Bluetooth chip, etc.

30

037000573961US

Processor 210 is also in communication with a data storage device 230. Data storage device 230 comprises an appropriate combination of magnetic, optical and/or semiconductor memory, and may include, for example, Random Access Memory (RAM), Read-Only Memory (ROM), a compact disc and/or a hard disk. Processor 210 and data storage device 230 may each be, for example: (i) located entirely within a single computer or other computing device; or (ii) connected to each other by a remote communication medium, such as a serial port cable, telephone line or radio frequency transceiver.

10

Data storage device 230 stores a program 215 for controlling processor 210. Processor 210 performs instructions of program 215, and thereby operates in accordance with the present invention, and particularly in accordance with the methods described in detail herein. Program 215 may be stored in a compressed, uncompiled and/or encrypted format. Program 215 furthermore includes program elements that may be necessary, such as an operating system, a database management system and "device drivers" for allowing processor 210 to interface with computer peripheral devices. Appropriate program elements are known to those skilled in the art, and need not be described in detail herein.

15

20

Data storage device 230 also stores at least one application program 225 which may be, for example, any of a number of commercially available or custom software programs known in the art. In an example which will be used herein to describe embodiments of the invention, application program 225 is an office productivity program such as a word processing program. Upon reading this disclosure, those skilled in the art will recognize that embodiments of the present invention may be used to correct or maintain a wide variety of types of software.

25

30

According to an embodiment of the present invention, the instructions of program 215 and application program 225 may be read into a main memory from another computer-readable medium, such from a ROM to RAM. Execution of sequences of the instructions in program 215 causes processor
5 210 to perform the process steps described herein. In alternative embodiments, hard-wired circuitry may be used in place of, or in combination with, software instructions for implementation of the processes of the present invention. Thus, embodiments of the present invention are not limited to any specific combination of hardware and software.

10

Data storage device 230 also stores, for example, error data 235 which may be used to identify potential corrective actions which may be taken using embodiments of the present invention. For example, error data 235 may include information identifying specific error code(s) which were encountered,
15 along with information identifying the conditions under which the error occurred. This information will be used, as will be described further below, to identify and take corrective action to fix the error. As will be described further below, some of the functionality described with respect to the controller 400 may be contained within user device 200, accordingly, some of the data
20 described in controller 400 may be stored in data storage device 230.

2. Vendor Device

FIG. 3 illustrates an embodiment of vendor device 300. In one
25 embodiment, vendor device 300 is a computing device, such as a server, operated by or on behalf of a software manufacturer or distributor. For example, vendor device 300 may be a Web-based server operated by a manufacturer of an application program which may be maintained, fixed, updated, and/or supported using techniques of the present invention.

30

Vendor device 300 may be implemented as a remote computer, a dedicated hardware circuit, an appropriately programmed general purpose computer, or any other equivalent electronic, mechanical or electro-mechanical device.

5

Vendor device 300 comprises a processor 310, such as one or more Intel® Pentium® processors. Processor 310 is coupled to a communication port 320 through which processor 310 communicates with other devices, such as, for example, one or more controllers 300. In some embodiments, vendor device 300 may communicate via communication port 320 with one or more user devices 200. Communication port 320 may include hardware and software facilitating communication with other devices using wired or wireless techniques, or a combination of different techniques. For example, communication port 320 may be one or more of: a network adapter, a modem, a Bluetooth chip, etc.

15

Processor 310 is also in communication with a data storage device 330. Data storage device 330 comprises an appropriate combination of magnetic, optical and/or semiconductor memory, and may include, for example, Random Access Memory (RAM), Read-Only Memory (ROM), a compact disc and/or a hard disk. Processor 310 and data storage device 330 may each be, for example: (i) located entirely within a single computer or other computing device; or (ii) connected to each other by a remote communication medium, such as a serial port cable, telephone line or radio frequency transceiver. In one embodiment, vendor device 300 may comprise one or more computers that are connected to a remote server computer for maintaining databases.

20

25

Data storage device 330 stores a program 315 for controlling processor 310. Processor 310 performs instructions of program 315, and thereby operates in accordance with the present invention, and particularly in

30

accordance with the methods described in detail herein. Program 315 may be stored in a compressed, uncompiled and/or encrypted format. Program 315 furthermore includes program elements that may be necessary, such as an operating system, a database management system and "device drivers" for
5 allowing processor 310 to interface with computer peripheral devices. Appropriate program elements are known to those skilled in the art, and need not be described in detail herein.

According to an embodiment of the present invention, the instructions
10 of program 315 may be read into a main memory from another computer-readable medium, such from a ROM to RAM. Execution of sequences of the instructions in program 315 causes processor 310 to perform the process steps described herein. In alternative embodiments, hard-wired circuitry may be used in place of, or in combination with, software instructions for
15 implementation of the processes of the present invention. Thus, embodiments of the present invention are not limited to any specific combination of hardware and software.

Data storage device 330 also stores patch data 325 and instruction
20 data 335. This information is used, as will be described in more detail below in conjunction with the description of data at controller 400, to identify an appropriate patch and supplemental instructions to fix an error at user device 200. Vendor device 300 and controller 400 may regularly share information to ensure that controller 400 has up to date information regarding all of the
25 patches and fixes made available by the vendor for software manufactured by that vendor.

As will be described further below, some of the functionality described with respect to the controller 400 may be contained within user device 200,
30 accordingly, some of the data described in controller 400 may be stored in data storage device 230.

3. Controller

Pro AS

~~FIG. 4 illustrates an embodiment of controller 400. In one embodiment,~~
5 controller 400 is operated by a service provider on behalf of one or more
software vendors, providers, or manufacturers to provide patches to a number
of user devices 200. In one embodiment, controller 400 is a Web-based
server in communication with one or more user devices 200 and one or more
vendor devices 300 via a network such as the Internet. Those skilled in the
10 art will recognize, upon reading this disclosure, that controller 400 may be
implemented as a system controller, a dedicated hardware circuit, an
appropriately programmed general purpose computer, or any other equivalent
electronic, mechanical or electro-mechanical device capable of providing the
functionality described herein. *AS*

15

Controller 400 comprises a processor 410, such as one or more Intel®
Pentium® processors. Processor 410 is coupled to a communication port 420
through which processor 410 communicates with other devices, such as, for
example, one or more user devices 200 and one or more vendor devices 300.
20 Communication port 420 may include hardware and software facilitation
communication with other devices using wired or wireless techniques, or a
combination of different techniques. For example, communication port 420
may be one or more of: a network adapter, a modem, a Bluetooth chip, etc.

25 Processor 410 is also in communication with a data storage device
430. Data storage device 430 comprises an appropriate combination of
magnetic, optical and/or semiconductor memory, and may include, for
example, Random Access Memory (RAM), Read-Only Memory (ROM), a
compact disc and/or a hard disk. Processor 410 and data storage device 430
30 may each be, for example: (i) located entirely within a single computer or
other computing device; or (ii) connected to each other by a remote

communication medium, such as a serial port cable, telephone line or radio frequency transceiver. In one embodiment, controller 400 may comprise one or more computers that are connected to a remote server computer for maintaining databases.

5

Data storage device 430 stores a program 415 for controlling processor 410. Processor 410 performs instructions of program 415, and thereby operates in accordance with the present invention, and particularly in accordance with the methods described in detail herein. Program 415 may be stored in a compressed, uncompiled and/or encrypted format. Program 415 furthermore includes program elements that may be necessary, such as an operating system, a database management system and "device drivers" for allowing processor 410 to interface with computer peripheral devices. Appropriate program elements are known to those skilled in the art, and need not be described in detail herein.

According to an embodiment of the present invention, the instructions of program 415 may be read into a main memory from another computer-readable medium, such from a ROM to RAM. Execution of sequences of the instructions in program 415 causes processor 410 to perform the process steps described herein. In alternative embodiments, hard-wired circuitry may be used in place of, or in combination with, software instructions for implementation of the processes of the present invention. Thus, embodiments of the present invention are not limited to any specific combination of hardware and software.

Data storage device 430 also stores a patch database 500 and an instruction database 600. The patch database 500 and the instruction database 600 are described in detail below and depicted with exemplary entries in the accompanying figures. As will be understood by those skilled in the art, the schematic illustrations and accompanying descriptions of the

5

1. Patch Database

10

15

20

30

be generated by, for example, individual vendors 300 or may be assigned by controller 300 to track different software programs.

Vendor 504 may be information identifying a particular vendor or
5 manufacturer of the application software identified by application identifier
502. In the embodiment depicted in FIG. 5, only a name of the vendor or
manufacturer is provided, however, other identifying information may also be
provided to identify the vendor, including, for example, a corporate address,
telephone number, or the like.

10

Version(s) 506 may be information identifying a particular version of the
application software identified by application identifier 502 for which a patch is
available.

15 Patch code(s) 508 may be information identifying a particular patch
available for the application software identified by application identifier 502.
Patch code(s) 508 may be assigned by, for example, a manufacturer of the
software identified by application identifier 502 or it may be assigned by an
entity operating controller 400. Patch code(s) 502 may be used, as will be
20 discussed below, to retrieve information regarding a patch from information
database 600.

Error code(s) 510 may be information identifying one or more error
codes to which the patch identified by patch code(s) 508 is responsive. Error
25 code(s) 510 may be any of a number of different codes including codes
specified by the manufacturer of the software which has an error. Those
skilled in the art appreciate that manufacturers and industry groups utilize a
number of application-specific error codes as well as a number of commonly-
used error codes. Any type of error code or other information used to identify
30 the particular circumstances regarding an error condition may be used.

Error description 512 includes information identifying a description of the error identified by error code(s) 510. This information may be provided to assist in the selection of an appropriate patch in response to an error. Entries in table 500 depict various types of error descriptions.

5

Some or all of the information from patch database 500 may be shared with or stored at user device 200 and/or vendor device 300.

2. Instruction Database

10

Referring to FIG. 6, a table represents information database 600 that may be stored at controller 400 according to an embodiment of the present invention. In some embodiments, all or portions of information database 600 may be stored at vendor device 300 and/or user device 200.

15

The table includes entries identifying information about patches which are available to correct errors that may be experienced by users of software. The table also defines fields 602, 604, and 606 for each of the entries. The fields specify: a patch code 602, a patch 604, and supplemental information 606. The data in information database 600 may be created and updated, for example, based on information received from individual vendors 300. For example, software manufacturers may generate patches for errors in their application software and provide the patches along with information regarding the patches to an entity operating controller 400.

25

Patch code 602 may be based on, or related to, patch code(s) 508 of patch database 500 (FIG. 5), and is used to identify individual patches which are available in system 100.

Patch 604 includes data such as executable code that implements the patch identified by patch code 602. Patch 604 may include, for example: a link to executable code, executable code, user instructions, or the like.

5 Supplemental information 606 includes information used to provide instructions or supporting information to a user operating a user device 200. This information 606 may be provided in conjunction with patch 604. Examples of different types of supplemental information 606 are depicted in the table of FIG. 6. In one embodiment, supplemental information 606 may
10 include advertising information or offers. For example, as depicted in the last row of table 600, an offer for a book related to a detected user error may be made. In this manner, embodiments of the present invention permit targeted advertising to be made to users who have particular needs. Other examples of advertisements may include offers to upgrade equipment (e.g., upgrade to
15 a newer version of a disk drive to solve a problem with an earlier version) or software (e.g., upgrade to the next version of application software).

Some or all of the information from information database 600 may be shared with or stored at user device 200 and/or vendor device 300.

Process Description

Reference is now made to FIG. 7, where a flow chart 700 is shown which represents the operation of an embodiment of the present invention.

25 The particular arrangement of elements in the flow chart of FIG. 7, is not meant to imply a fixed order to the steps; embodiments of the present invention can be practiced in any order that is practicable. After a description of the flow chart 700, several illustrative examples will be presented to facilitate understanding of embodiments of the present invention.

At 704 processing continues and system 100 identifies the error experienced by user device 200. In one embodiment, this identification is performed by controller 400 by comparing the error code and/or information identifying the conditions under which the error occurred with stored error information (e.g., information in patch database 500). In other embodiments, the identification may be performed by user device 200 or vendor device 300. Once the error has been identified, processing continues at 706 where a potential corrective action is identified. In one embodiment, this involves identifying one or more patch codes (item 508 of FIG. 5) identifying one or more patches which are provided by an entity such as the manufacturer of the software to correct the error.

19

10

15

20

30

400 may receive payment from either the user or the software vendor for each fix provided. This payment may be a set amount per fix or it may vary based on the nature of the fix. In some embodiments, advertisements or other solicitations may be provided along with the fix at 710.

5

Although the present invention has been described with respect to a preferred embodiment thereof, those skilled in the art will note that various substitutions may be made to those embodiments described herein without departing from the spirit and scope of the present invention.

10

0976557E 021601